

LED PANEL LIGHT



# ALPHA3060



Ultra HD  
Lighting Quality



High CRI  
True Color



High TLCI  
True Color



Flicker Free



Smart Touch  
Control



USB Firmware  
Upgrade



Long  
LED Lifetime

## ■ Fixture Information

- Flat light source lighting fixture, which is mainly used in broadcasting studios
- Light that does not expose the light source, with less glare, evenly and extremely soft light distribution
- Excellent light quality, and average CRI 95~98 / R9, R12 are CRI 90 or higher
- Beam cutting is excellent by adjusting the angle of the barn-door
- Measured same LUX data at both 3200K / 5600K which shows stable and reliable Optical Technique
- High efficiency and light saturation by using Micro diffusing lens, and excellent photometric flatness
- 2500~10000K color temperature control function
- R, G, B Full Color LEDs are combined to create a scene for all acting parts and a variety of atmospheres
- Support RDM network communication and various mode setting possible
- Smart touch control method makes it easy and convenient to check all information at a glance
- The materials are made by metal, has good ability to reduce heat, and has the slot to install the soft(diffusing) filter
- Housing is designed for easy maintenance and repair
- Long life, reduces maintenance costs and power consumption

## ■ Technical Specifications

Power Input Voltage	AC 100 ~ 240V, 50/60Hz
Power Consumption (Max)	400W
LED Chip	0.5W / Full RGB + W LED
Beam Angle	90°
Color Temperature	Full 2,500 ~ 10,000K (VCT)
Colored Light	Full RGB + W (4 Color Gamut with Hue and Saturation Control)
Dimming	0~100% 16-bit
Supported Protocols	DMX512 / DMX512 RDM / <b>Option</b> Wireless DMX512 / Wireless RDM
Component	4-leaf barn door + Clamp + Manual yoke + Safety Chain / <b>Option</b> Pole Operation pan & tilt yoke
Dimension (mm / inch)	792 x 441 x 204 / 31.2 x 17.4 x 8 (WHD)
Weight (kg / lbs)	13.5 / 29.8

## ■ Photometric Diagram

